

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Engine Oil SAE 10W-30
Article number: 104912, 104913
UFI: Y5JC-X9NP-Y008-V88C

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Engine oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG
Wilhelmstr. 47
58256 Ennepetal / GERMANY
Phone +49 2333 911-0
Fax +49 2333 911-444
Homepage www.febi.com
E-mail info@febi.com

Address enquiries to

Technical information info@febi.com

Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P273 Avoid release to the environment.
P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

2.3 Other hazards

Human health dangers

Frequent persistent contact with the skin can cause skin irritation.

Environmental hazards

Does not contain any PBT or vPvB substances.
Contains no ingredients with endocrine-disrupting properties.

Other hazards

none

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
1 - <2,5	Phenol, dodecyl-, sulfoniert, Carbonate, Calciumsalze, überbasisch CAS: 68784-26-9, EINECS/ELINCS: 272-234-3, Reg-No.: 01-2119524004-56-XXXX GHS/CLP: Aquatic Chronic 4: H413
1 - <2,5	Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt) CAS: 64742-65-0, EINECS/ELINCS: 265-169-7, Reg-No.: 01-2119471299-27-XXXX GHS/CLP: Asp. Tox. 1: H304
<0,1	phenol, (tetrapropenyl) derivatives CAS: 74499-35-7, EINECS/ELINCS: 616-100-8 GHS/CLP: Repr. 1B: H360F - Skin Corr. 1C: H314 - Eye Dam. 1: H318 - Aquatic Acute 1: H400 - Aquatic Chronic 1: H410, M-Factor (acute): 10, M-Factor (chronic): 10

Comment on component parts

For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Take off contaminated clothing and wash before reuse.

Inhalation

Ensure supply of fresh air.
In the event of symptoms seek medical treatment.

Skin contact

In case of contact with skin wash off immediately with soap and water.
Consult a doctor if skin irritation persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion

Consult a doctor immediately.
Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Fire extinguishing method of surrounding areas must be considered.
Foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not be used

Full water jet

5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.
Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.
Ensure adequate ventilation.
Use personal protective equipment (protective gloves, safety glasses, protective clothing).

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).
Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.
Do not smoke.
Fire class (DIN EN 2): B
Do not eat, drink or smoke when using this product.
Use barrier skin cream.
Wash hands before breaks and after work.
Cloths contaminated with product should not be kept in trouser pockets.
Contaminated work clothing should not be allowed out of the workplace.
Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Keep container tightly closed.
Keep container in a well-ventilated place.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (UK)

not relevant

Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

DNEL

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, oral, Long-term - local effects, 740 µg/kg bw/day
Phenol, dodecyl-, sulfoniert, Carbonate, Calciumsalze, überbasisch, CAS: 68784-26-9
There are no DNEL values established for the substance.

PNEC

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
oral (food), 9,33 mg/kg food
Phenol, dodecyl-, sulfoniert, Carbonate, Calciumsalze, überbasisch, CAS: 68784-26-9
There are no PNEC values established for the substance.

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances. General exposure limit for oil mist should be noted.
Eye protection	If there is a risk of splashing: safety glasses (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,4 mm; Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	light protective clothing
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection. Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)
Thermal hazards	none
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	liquid
Color	brown
Odor	characteristic
Odour threshold	not relevant
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point or initial boiling point and boiling range [°C]	No information available.
Flash point [°C]	>240 (ISO 2592)
Flammability	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/cm ³]	0,86 (DIN 51757) (15 °C / 59,0 °F)
Relative density	not determined
Bulk density [kg/m ³]	not applicable
Solubility in water	immiscible
Solubility other solvents	No information available.
Partition coefficient n-octanol/water (log value)	No information available.
Kinematic viscosity	>20,5 mm ² /s (40° C) ca. 12 mm ² /s (100°C) (DIN 51562/T1)
Relative vapour density	No information available.
Melting point [°C]	No information available.
Auto-ignition temperature [°C]	No information available.
Decomposition temperature [°C]	No information available.
Particle characteristics	No information available.

9.2 Other information

Pour point: ca. 33°C

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating.



Ferdinand Bilstein GmbH + Co. KG

Date printed 05.03.2024, Revision 05.03.2024

Version 5.0

Page 6 / 12

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity Based on available data, the classification criteria are not met.

Product
ATE-mix, oral, >2000 mg/kg bw
Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, oral, Rat, 5000 mg/kg bw
phenol, (tetrapropenyl) derivatives, CAS: 74499-35-7
LD50, oral, Rat, 2200 mg/kg bw, OECD 401

Acute dermal toxicity Based on available data, the classification criteria are not met.

Product
ATE-mix, dermal, >2000 mg/kg bw
Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, dermal, Rabbit, > 2000 - 5000 mg/kg bw
phenol, (tetrapropenyl) derivatives, CAS: 74499-35-7
LD50, dermal, Rabbit, 15000 mg/kg bw, OECD 402

Acute inhalational toxicity Based on available data, the classification criteria are not met.

Product
ATE-mix, inhalation (vapour), >20 mg/L
Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LC50, inhalative, Rat, 2,18 - 5,53 mg/L air 4h, 4h

Serious eye damage/irritation Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Eye, non-irritating

Skin corrosion/irritation Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-irritating

Respiratory or skin sensitisation Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-sensitizing

Specific target organ toxicity — single exposure Based on the available information, the classification criteria are not fulfilled.



Ferdinand Bilstein GmbH + Co. KG

Date printed 05.03.2024, Revision 05.03.2024

Version 5.0

Page 8 / 12

Specific target organ toxicity — repeated exposure Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOAEL, inhalative, Rat, 980 mg/m ³ air, no adverse effect observed
LOAEL, dermal, mouse, 100 mg/kg bw/day, The effects observed are not sufficient for classification.
LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.

Mutagenicity Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
in vitro, negativ

Reproduction toxicity Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed

- Development No information available.

Carcinogenicity Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard Based on the available information, the classification criteria are not fulfilled.
 On basis of test data

General remarks Frequent persistent contact with the skin can cause skin irritation.
 Toxicological data of complete product are not available.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties Contains no ingredients with endocrine-disrupting properties.

11.2.2 Other information none

SECTION 12: Ecological information

12.1 Toxicity

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOELR, (14d), fish, 1 g/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), fish, 100 mg/L

12.2 Persistence and degradability

Behaviour in environment compartments not determined

Behaviour in sewage plant not determined

Biological degradability not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Ecological data of complete product are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

In according to RoHS!
Coordinate disposal with the disposal contractor/authorities if necessary.

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

Ferdinand Bilstein GmbH + Co. KG

Date printed 05.03.2024, Revision 05.03.2024

Version 5.0 Page 10 / 12

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	2008/98/EG (2000/532/EG); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EG) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EWG ((EG) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021
- Comment on component parts	Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
- Annex I (REACH)	The product is not subject to Annex I restrictions.
- Annex XIV (REACH)	According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain any substances \geq 0.1% that are subject to authorisation.
- Annex XVII (REACH)	According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product contains \geq 0.1% of substances with the following restrictions. 75 According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is not subject to any restrictions.
TRANSPORT-REGULATIONS	ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)
NATIONAL REGULATIONS (UK):	EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.
- Observe employment restrictions for people	no
- VOC (2010/75/CE)	0 %

15.2 Chemical safety assessment

For this product a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H318 Causes serious eye damage.
H314 Causes severe skin burns and eye damage.
H410 Very toxic to aquatic life with long lasting effects.
H400 Very toxic to aquatic life.
H360F May damage fertility.
H304 May be fatal if swallowed and enters airways.
H413 May cause long lasting harmful effects to aquatic life.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV@TWA = Threshold limit value – time-weighted average
TLV@STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)

Modified position

1.3, 3.2, 5.1, 6.1, 8.1, 8.2, 9.1, 9.2, 11.1, 11.2, 12.6, 12.7, 13.1, 15.1, 16.2, 16.3