antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 25.07.2024, Revision 16.05.2024 Version 8.0 Page 1 / 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

antifreeze G12+ (-35°C Ready Mix) Article number: 172009, 172010, 172011

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Anti-freezing agents

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Acute Tox. 4: H302 Harmful if swallowed.

STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure if

swallowed. (kidneys)

2.2 Label elements

Signal word

The product is classified as hazardous in accordance to OSHA Standard 29 CFR 1910.1200

(HCS 2024)

Hazard pictograms



WARNING

Contains: Ethylene glycol, CAS: 107-21-1

Hazard statements H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P260 Do not breathe vapors.

P270 Do no eat, drink or smoke when using this product.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of

disposal.



antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

2.3 Other hazards

Environmental hazards Contains no ingredients with endocrine-disrupting properties (≥ 0,1%).

This substance/mixture contains no components considered to be either persistent,

bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels

of 0.1% or higher.

Other hazards Further hazards were not determined with the current level of knowledge.

This product is classified as hazardous in accordance to OSHA Standard 29 CFR 1910.1200.

SECTION 3: Composition / Information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
40 - <50	Ethylene glycol
	CAS: 107-21-1

Comment on component parts

For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Change soaked clothing.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

Ingestion Consult a doctor immediately.

Rinse out mouth and give plenty of water to drink.

Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Tiredness Unconsciousness Headache Vertigo

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide.

Water spray jet. Dry powder. Foam.

Extinguishing media that must not

be used

Full water jet.

antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 25.07.2024, Revision 16.05.2024

Version 8.0

Page 3 / 13

5.2 Special hazards arising from the substance or mixture

risk of formation of toxic pyrolysis products, carbon monoxide (CO), not combusted hydrocarbons

5.3 Advice for firefighters

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

High risk of slipping due to leakage/spillage of product.

Use personal protective equipment (protective gloves, safety glasses, protective clothing).

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Pick up with absorbent material (e.g. sand, sawdust, universal absorbent, diatomaceous

earth).

Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provide solvent-resistant and impermeable floor.

Use solvent-resistant equipment.

Use only in well-ventilated areas.

Remove soiled or soaked clothing immediately.

Do not eat, drink or smoke when using this product.

Wash hands before breaks and after work.

Use barrier skin cream.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Do not store together with food and animal food/diet.

Protect from heat/overheating and from sun.

Keep container in a well-ventilated place.

Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2

antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (US)

Not applicable

DNEL

Ethylene glycol, CAS: 107-21-1

Industrial, inhalative, Long-term - local effects, 35 mg/m³

Industrial, dermal, Long-term - systemic effects, 106 mg/m³

general population, inhalative, Long-term - local effects, 7 mg/m³

general population, dermal, Long-term - systemic effects, 53 mg/m³

PNEC

Ethylene glycol, CAS: 107-21-1

sediment (seawater), 3,7 mg/kg

sewage treatment plants (STP), 199,5 mg/l (AF=10)

soil, 1,53 mg/kg

sediment (freshwater), 37 mg/kg

seawater, 1 mg/L

freshwater, 10 mg/L

8.2 Exposure controls

Additional advice on system design
Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

Eye protection Safety glasses. (EN 166:2001)

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information

0,45 mm Nitrile rubber, >480 min (EN 374-1/-2/-3).

Skin protection Protective clothing (EN 340)

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

Respiratory protection In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear

appropriate respiratory protection.

Short term: filter apparatus, combination filter A-P2.

Thermal hazards None

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 25.07.2024, Revision 16.05.2024 Version 8.0 Page 5 / 13

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical stateLiquidFormLiquidColorred

Odor characteristic

Odor threshold No information available.

pH-value 7,5 - 10

pH-value [1%] Not determined

Boiling point or initial boiling point

and boiling range [°C]

>108

Flash point [°C] >125 (c.c. ISO 2719)
Flammability Not applicable
Lower explosion limit 4,9 Vol.%
Upper explosion limit 14,6 Vol.%

Oxidizing properties No

Vapor pressure/gas pressure [kPa] Not determined

Density [g/cm³] 1,060

Relative density No information available.

Bulk density [kg/m³] Not applicable
Solubility in water Miscible

Solubility other solvents No information available.

Partition coefficient n-octanol/water

(log value)

-1,93

Kinematic viscosityNo information available.Relative vapour densityNo information available.

Melting point [°C] Not determined

Auto-ignition temperature [°C] >40

Decomposition temperature [°C] No information available.

Particle characteristics No information available.

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

Reactions with acids.

Reactions with strong alkalies.

10.4 Conditions to avoid

Strong heating.

antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 25.07.2024, Revision 16.05.2024

Version 8.0

Page 6 / 13

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 25.07.2024, Revision 16.05.2024

Version 8.0

Page 7 / 13

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity

Based on the information available, the classification criteria have been fulfilled.

Product

ATE-mix, oral, 600,2 mg/kg bw

Substance

Ethylene glycol, CAS: 107-21-1

LD50, oral, Rat, 7712 mg/kg bw

ATE, oral, 500 mg/kg (Acute Tox. 4)

Acute dermal toxicity

Based on the information available, the classification criteria have not been fulfilled.

Product

ATE-mix, dermal, >2000 mg/kg bw

Substance

Ethylene glycol, CAS: 107-21-1

LD50, dermal, mouse, > 3500 mg/kg bw

Acute inhalational toxicity

Based on the information available, the classification criteria have not been fulfilled.

Product

ATE-mix, inhalative, >20 mg/L

Substance

Ethylene glycol, CAS: 107-21-1

LC50, inhalative, Rat, > 2,5 mg/L air, 6h

Serious eye damage/irritation

Based on the information available, the classification criteria have not been fulfilled.

Substance

Ethylene glycol, CAS: 107-21-1

Eye, Rabbit, In vivo study, non-irritating

Skin corrosion/irritation

Based on the information available, the classification criteria have not been fulfilled.

Substance

Ethylene glycol, CAS: 107-21-1

dermal, Rabbit, In vivo study, non-irritating

Respiratory or skin sensitisation

Based on the information available, the classification criteria have not been fulfilled.

Substance

Ethylene glycol, CAS: 107-21-1

dermal, Guinea pig, In vivo study, non-sensitizing

Specific target organ toxicity — single exposure

Based on the information available, the classification criteria have not been fulfilled.

Specific target organ toxicity — repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Substance

Ethylene glycol, CAS: 107-21-1

antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 25.07.2024, Revision 16.05.2024

Version 8.0

Page 8 / 13

NOAEL, dermal, dogs, 2200 mg/kg bw/day, adverse effect observed

NOEL, oral, Rat, 150 mg/kg bw/day, OECD 408, adverse effect observed

Mutagenicity

Based on the information available, the classification criteria have not been fulfilled.

Substance

Ethylene glycol, CAS: 107-21-1

in vitro, OECD 471, no adverse effect observed

Reproduction toxicity

Based on the information available, the classification criteria have not been fulfilled.

- Fertility

Substance

Ethylene glycol, CAS: 107-21-1

NOAEL, oral, Rat, > 1000 mg/kg bw/day, no adverse effect observed

- Development

Substance

Ethylene glycol, CAS: 107-21-1

NOAEL, oral, Rat, 500 mg/kg bw/day, no adverse effect observed

Carcinogenicity

Based on the information available, the classification criteria have not been fulfilled.

Substance

Ethylene glycol, CAS: 107-21-1

NOAEL, oral, Rat, 1000 mg/kg bw/day, In vivo study, no adverse effect observed

Aspiration hazard

Based on the information available, the classification criteria have not been fulfilled.

General remarks

Toxicological data of complete product are not available.

SECTION 12: Ecological information

12.1 Toxicity

Substance

Ethylene glycol, CAS: 107-21-1

LC50, (3d), fish, 72.86 g/L

LC50, (28d), fish, 1,5 g/L

EC50, (48h), Invertebrates, 100 mg/L

EC50, (21d), Invertebrates, 33,911 g/L

EC50, (4d), Invertebrates, 3,536 - 13 g/L

12.2 Persistence and degradability

Behaviour in environment compartments

Behaviour in sewage plant

Biological degradability

No information available.

12.3 Bioaccumulative potential

Product has having no bioaccumulation potential.

antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 25.07.2024, Revision 16.05.2024

Version 8.0

Page 9 / 13

12.4 Mobility in soil

The product is mobile in an aqueous environment.

12.5 Results of PBT and vPvB assessment

Does not contain any relevant substances fulfilling the classification criteria.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties (≥ 0,1%).

12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Dispose of as hazardous waste.

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

RCRA Hazard Class (40CFR 261)

Waste must be disposed of in accordance with federal, state and local environmental control

regulations. Consult your local or regional authorities.

SECTION 14: Transport

14.1 UN number

Transport by land according to

ADR/RID

Not applicable

Inland navigation (ADN) Not applicable

Marine transport in accordance with

IMDG

Not applicable

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 Not applicable

CFR)

antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 25.07.2024, Revision 16.05.2024

Version 8.0 Page 10 / 13

14.2 UN proper shipping name

Transport by land according to ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN)

NO DANGEROUS GOODS

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

IMDG

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

DOT Road Shipment Information (49 Not applicable

CFR)

14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

Not applicable

Inland navigation (ADN)

Not applicable

Marine transport in accordance with Not applicable

IMDG

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 Not applicable

CFR)

14.4 Packing group

Transport by land according to

ADR/RID

Not applicable

Inland navigation (ADN)

Not applicable

Marine transport in accordance with Not applicable

IMDG

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 Not applicable

CFR)

antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 25.07.2024, Revision 16.05.2024 Version 8.0 Page 11 / 13

14.5 Environmental hazards

Transport by land according to ADR/RID

No

Inland navigation (ADN)

No

Marine transport in accordance with

IMDG

Air transport in accordance with IATA No

DOT Road Shipment Information (49 No

CFR)

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

US Regulations

National regulations 29 CFR 1910.1200-HCS 2012, OSHA-PEL, ACGIH-TLV, NTP, IARC, SARA Title III, NFPA,

TSCA, California - Prop. 65

- SARA, 302

- SARA, 311

- SARA, 313

- CA Proposition 65 Some chemical substances Ethylene gylcol (ingested)- CAS 107-21-1 in this material are

named in California-P65 list.



WARNING: This product can expose you to chemicals including "Ethylene gylcol (ingested)-CAS 107-21-1", which is known to the State of California to cause birth defects or other

reproductive harm. For more information go to www.P65Warnings.ca.gov.'

- TSCA All chemical substances in this material are included on or exempted from listing on the TSCA

Inventory.

- FDA

American Conference of

Not determined

Governmental Industrial Hygienists -

ACGIH

International Agency for Research on Does not contain any relevant substances fulfilling the classification criteria.

Cancer IARC

National Toxicology Program - NTP

This product is named NTP - National Toxicology Program (contains Ethylene gylcol).

HAP-VOC

Transport-regulations DOT-Classification, ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)

15.2 Chemical safety assessment

Not applicable

antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 25.07.2024, Revision 16.05.2024

Version 8.0 Page 12 / 13

SECTION 16: Other information

16.1 Abbreviations and acronyms:

ACGIH = American Conference of Governmental Industrial Hygienists;

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route;

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses;

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure:

CAS = Chemical Abstracts Service;

CERCLA = Comprehensive Environmental Response, Compensation and Liability Act;

CFR = Code of Federal Regulations;

CPR = Controlled Products Regulations;

DMEL = Derived Minimum Effect Level;

DNEL = Derived No Effect Level;

DOT = Department of Transportation;

EC50 = Median effective concentration;

EPA = Environmental Protection Agency;

GHS = Globally Harmonized System of Classification and Labelling of Chemicals;

IATA = International Air Transport Association;

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk;

IC50 = Inhibition concentration, 50%;

IMDG = International Maritime Code for Dangerous Goods;

IARC = International Agency of Research on Cancer;

IATA = International Air Transport Association;

TSCA = Toxic Substance Control Act;

HMIS = Hazardous Materials Identification System;

NFPA = National Fire Protection Association;

NIOSH = National Institute for Occupational Safety and Health;

OSHA = Occupational Safety and Health Administration;

LC50 = Lethal concentration, 50%;

LD50 = Median lethal dose, 50%;

MARPOL = International Convention for the Prevention of Marine Pollution from Ships;

PBT = Persistent, Bioaccumulative and Toxic substance;

PNEC = Predicted No-Effect Concentration;

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals;

SARA = Superfund Amendments and Reauthorization Act;

TLV®/TWA = Threshold limit value – time-weighted average; TLV®STEL = Threshold limit value – short-time exposure limit;

VOC = Volatile Organic Compounds;

vPvB = very Persistent and very Bioaccumulative;

16.2 Ratings

antifreeze G12+ (-35°C Ready Mix) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 25.07.2024, Revision 16.05.2024

Version 8.0 Page 13 / 13

NFPA Ratings



TOP, FLAMMABILITY: 1 - Slight Hazard LEFT, HEALTH: 2 - Moderate Hazard RIGHT, REACTIVITY: 0 - Minimal Hazard BOTTOM, SPECIAL NOTICE: -

HMIS Ratings



- 2*- Moderate chronic Hazard
- 1 Slight Hazard
- 0 Minimal Hazard
- X Personal protection rating to be supplied by user depending on use conditions

PERSONAL PROTECTION:

- A Safety Glasses
- B Safety Glasses and Gloves
- C Safety Glasses, Gloves and Protection Apron
- D Face Shield, Gloves and Protection Apron
- E Safety Glasses, Gloves and Dust Respirator
- F Safety Glasses, Gloves, Protection Apron and Dust Respirator
- G Safety Glasses, Gloves and Vapor Respirator.
- H Splash Goggles, Gloves, Protection Apron and Vapor Respirator.
- I Safety Glasses, Gloves, Dust Respirator and Vapor Respirator.
- J Splash Goggles, Gloves, Protection Apron, Dust Respirator and Vapor Respirator.
- K Airline Mask or Hood, Gloves, Full Suit and Boots.
- X Personal protection rating to be supplied by user depending on use conditions

Modified position

None