Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0

Page 1 / 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Gear oil 75W - 90 Article number: 32590

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Lubricant

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

No classification.

2.2 Label elements

The product is classified as hazardous in accordance to OSHA Standard 29 CFR 1910.1200

(HCS 2012)

Hazard pictograms None
Signal word None
Hazard statements None
Precautionary statements None

Special labelling EUH210 Safety data sheet available on request.

Contains: Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), EC / List no. 931-

384-6. EUH208 May produce an allergic reaction.

2.3 Other hazards

Physico-chemical hazards No particular hazards known.

Environmental hazards Does not contain any PBT or vPvB substances.

Contains no ingredients with endocrine-disrupting properties.

Other hazards No particular hazards known.

This product is classified as non-hazardous in accordance to OSHA Standard 29 CFR

1910.1200.

Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0

Page 2 / 14

SECTION 3: Composition / Information on ingredients

Substances

Not applicable

3.2 **Mixtures**

The product is a mixture.

Range [%]	Substance
20 - < 50	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
	CAS: 72623-87-1
1 - < 4,5	Polysulfide, Di-tert-butyl-
	CAS: 68937-96-2
0,1 - < 1	Magnesium metaborate
	CAS: 13703-82-7
1 - < 2,5	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), EC / List no. 931-384-6

For full text of H-statements and R-phrases: see SECTION 16. Comment on component parts

Contains less than 3% w/w DMSO-extract (only for mineral oils)

SECTION 4: First aid measures

Description of first aid measures

General information Change soaked clothing.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with plenty of water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Consult a doctor immediately.

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

Extinguishing media

Suitable extinguishing media Foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not

be used

Full water jet.

Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

Carbon monoxide (CO) Sulphur oxides (SOx). Nitrogen oxides (NOx).

Gear oil 75W - 90 Article number 32590



Page 3 / 14

Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. oil binder).

Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures necessary if used correctly.

Use only in well-ventilated areas.

Use solvent-resistant equipment.

Do not eat, drink or smoke when using this product.

After worktime and before work breaks the affected skin areas must be thoroughly cleaned.

Use barrier skin cream.

Cloths contaminated with product should not be kept in trouser pockets.

Take off contaminated clothing and wash before reuse.

Contaminated work clothing should not be allowed out of the workplace.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Keep container tightly closed.

Keep container in a well-ventilated place.

7.3 Specific end use(s)

See product use, SECTION 1.2

Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0

Page 4 / 14

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (US)

Substance

1-Decene, homopolymer, hydrogenated

CAS: 68037-01-4

Long-term exposure: 5 mg/m³, OSHA PEL

DNEL

Substance

Polysulfide, Di-tert-butyl-, CAS: 68937-96-2

No DNEL values could be derived for the substance with respect to systemic effects.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³

Industrial, inhalative, Long-term - local effects, 5.58 mg/m³

Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day

general population, inhalative, Long-term - local effects, 1.19 mg/m³

general population, inhalative, Long-term - systemic effects, 740 µg/kg bw/day

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), EC / List no. 931-384-6

Industrial, inhalative, Long-term - systemic effects, 4.28 mg/m³ (AF=30)

Industrial, dermal, Long-term - systemic effects, 12.5 mg/kg bw/d (AF=120)

general population, dermal, Long-term - systemic effects, 6.25 mg/kg bw/d (AF=240)

general population, oral, Long-term - systemic effects, 0.25 mg/kg bw/d (AF=600)

general population, inhalative, Long-term - systemic effects, 1.09 mg/m³ (AF=60)

Magnesium metaborate, CAS: 13703-82-7

Industrial, inhalative, Long-term - systemic effects, 5.49 mg/m³

Industrial, dermal, Long-term - systemic effects, 7.78 mg/kg bw/day

general population, inhalative, Long-term - systemic effects, 0.82 mg/m³

general population, dermal, Long-term - systemic effects, 0.278 mg/kg bw/day

general population, oral, Long-term - systemic effects, 0.28 mg/kg bw/day

PNEC

Substance

Polysulfide, Di-tert-butyl-, CAS: 68937-96-2

There are no PNEC values established for the substance

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

oral (food), 9.33 mg/kg food

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), EC / List no. 931-384-6

freshwater, 2.4 µg/L (AF=50)

seawater, 0.24 µg/L (AF=500)

sewage treatment plants (STP), 24.33 mg/L (AF=100)

sediment (freshwater), 12.9 µg/kg dw

sediment (seawater), 1.29 µg/kg dw

soil, 1.17 µg/kg dw

oral (food), 10 mg/kg dw (AF=300)

Magnesium metaborate, CAS: 13703-82-7

freshwater, 0.05 mg/L

Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0 Page 5 / 14

seawater, 0.05 mg/L

sewage treatment plants (STP), 100 mg/L

sediment (freshwater), 1.38 mg/kg sediment dw

sediment (seawater), 1.38 mg/kg sediment dw

soil, 0.247 mg/kg soil dw

oral (food), 1.67 mg/kg food

8.2 Exposure controls

Additional advice on system design
Ensure adequate ventilation on workstation.

General limit for oil mist should be noted.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

Eye protection Safety glasses. (EN 166:2001)

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

> 0,4 mm: Nitrile rubber, >120 min (EN 374-1/-2/-3).

Skin protection Light protective clothing.

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Do not inhale gases/vapors/aerosols. Avoid contact with eyes and skin.

Respiratory protection Not applicable

Thermal hazards No information available.

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0

Page 6 / 14

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical stateLiquidFormLiquidColorbrownOdorcharacteristic

Odor threshold No information available.

pH-valuepH-value [1%]Not applicable

Boiling point or initial boiling point

and boiling range [°C]

No information available.

Flash point [°C] 210 (EN ISO 2592 (COC))
Flammability No information available.
Lower explosion limit No information available.
Upper explosion limit No information available.

Oxidizing properties No

Vapor pressure/gas pressure [kPa] No information available.

Density [g/cm³] 0,86 (DIN 51757) (15 °C / 59,0 °F)

Relative density

Bulk density [kg/m³]

Not applicable

Solubility in water

Not applicable

Solubility other solvents No information available.

Partition coefficient n-octanol/water No information available.

(log value)

Kinematic viscosity 113,9 mm²/s (40°C) (DIN 51562) **Relative vapour density** No information available.

Melting point [°C] No information available.

Auto-ignition temperature [°C] Not applicable

Decomposition temperature [°C]No information available.Particle characteristicsNo information available.

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

The product is stable under standard conditions.

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

No special measures necessary.

Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0

Page 7 / 14

10.5 Incompatible materials

Strong oxidizing agent. Strong basic compounds strong acids

10.6 Hazardous decomposition products

No hazardous decomposition products known.

Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0

Page 8 / 14

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity

Product

ATE-mix, oral, > 5000 mg/kg bw

Substance

Polysulfide, Di-tert-butyl-, CAS: 68937-96-2

No information available.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

LD50, oral, Rat, 5000 mg/kg bw

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), EC / List no. 931-384-6

LD50, oral, Rat, 2000 mg/kg

Magnesium metaborate, CAS: 13703-82-7

LD50, oral, Rat, >2000 mg/kg bw (OECD 420)

Acute dermal toxicity

Product

dermal, Based on the information available, the classification criteria have not been fulfilled.

Substance

Polysulfide, Di-tert-butyl-, CAS: 68937-96-2

No information available.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw

Magnesium metaborate, CAS: 13703-82-7

LD50, dermal, Rat, 2000 mg/kg bw

Acute inhalational toxicity

Product

inhalative, Based on the information available, the classification criteria have not been fulfilled.

Substance

Polysulfide, Di-tert-butyl-, CAS: 68937-96-2

No information available.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1

LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Serious eye damage/irritation Based on the information available, the classification criteria have not been fulfilled.

Non-irritant.

The classification occurred based on substance-specific concentration limits.

Skin corrosion/irritationToxicological data of complete product are not available.

No classification. Calculation method

Respiratory or skin sensitisation Non-sensitizing.

On basis of test data

Specific target organ toxicity —

single exposure

Based on the information available, the classification criteria have not been fulfilled.

Specific target organ toxicity — Based on the information available, the classification criteria have not been fulfilled.

Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0 Page 9 / 14

repeated exposure

Substance	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1	
NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day	
NOAEC, inhalative, Rat, 980 mg/m³ air	
LOAEL, oral, Rat, 125 mg/kg bw/day	
Magnesium metaborate, CAS: 13703-82-7	
NOAEL, oral, Rat, 125 mg/kg bw/day	

MutagenicityBased on the information available, the classification criteria have not been fulfilled.Reproduction toxicityBased on the information available, the classification criteria have not been fulfilled.CarcinogenicityBased on the information available, the classification criteria have not been fulfilled.Aspiration hazardBased on the information available, the classification criteria have not been fulfilled.

General remarks

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

SECTION 12: Ecological information

12.1 Toxicity

Product		
Based on the information available, the classification criteria have not been fulfilled.		
Substance		
Polysulfide, Di-tert-butyl-, CAS: 68937-96-2		
EC50, (72h), Algae, 100 mg/L		
EL50, (48h), Invertebrates, 63 mg/L		
NOELR, (48h), Invertebrates, 18 mg/L		
NOELR, (72h), Algae, 100 mg/L		
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1		
NOELR, (14d), fish, 1 g/L		
LL50, (4d), Invertebrates, 10 g/L		
LL50, (4d), fish, 100 mg/L		
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), EC / List no. 931-384-6		
LC50, (96h), fish, 24 mg/l		
EC50, (48h), Daphnia magna, 91,4 mg/l		
Magnesium metaborate, CAS: 13703-82-7		
EL50, (24h), Daphnia magna, >50mg/l (OECD 202)		
EL50, (72h), Pseudokirchneriella subcapitata, >50mg/l (OECD 201)		
LL50, (96h), Oncorhynchus mykiss, >50mg/l (OECD 203)		

12.2 Persistence and degradability

Behaviour in environment compartments

Behaviour in sewage plant Not determined
Biological degradability Not determined

bfe00077

Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0

Page 10 / 14

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

In according to RoHS!

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

RCRA Hazard Class (40CFR 261)

Waste must be disposed of in accordance with federal, state and local environmental control

regulations. Consult your local or regional authorities.

SECTION 14: Transport

14.1 UN number

Transport by land according to

ADR/RID

Not applicable

Inland navigation (ADN) Not applicable

Marine transport in accordance with

IMDG

Not applicable

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 Not applicable

CFR)

Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0

Page 11 / 14

14.2 UN proper shipping name

Transport by land according to ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN)

NO DANGEROUS GOODS

IMDG

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

DOT Road Shipment Information (49 NOT CLASSIFIED AS "DANGEROUS GOODS"

CFR)

14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

Not applicable

Inland navigation (ADN)

Not applicable

Marine transport in accordance with Not applicable

IMDG

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 Not applicable

CFR)

14.4 Packing group

Transport by land according to

ADR/RID

Not applicable

Inland navigation (ADN)

Not applicable

Marine transport in accordance with Not applicable

IMDG

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 Not applicable

CFR)

Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024 Version 12.0. Supersedes version: 10.0 Page 12 / 14

14.5 Environmental hazards

Transport by land according to

ADR/RID

No

Inland navigation (ADN) No

Marine transport in accordance with

IMDG

Air transport in accordance with IATA No

DOT Road Shipment Information (49 No

CFR)

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

US Regulations

National regulations 29 CFR 1910.1200-HCS 2012, OSHA-PEL, ACGIH-TLV, NTP, IARC, SARA Title III, NFPA,

TSCA, California - Prop. 65

- SARA, 302 No information available. - SARA, 311 No information available. - SARA, 313 No information available.

- TSCA All chemical substances in this material are included on or exempted from listing on the TSCA

Inventory.

- FDA No information available.

American Conference of

Governmental Industrial Hygienists -

ACGIH

Ingredients not listed as carcinogens.

Cancer IARC

International Agency for Research on No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

National Toxicology Program - NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

HAP-VOC No information available.

DOT-Classification, ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024) **Transport-regulations**

15.2 Chemical safety assessment

For this product a chemical safety assessment has not been carried out.

Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0 Page 13 / 14

SECTION 16: Other information

16.1 Abbreviations and acronyms:

ACGIH = American Conference of Governmental Industrial Hygienists;

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route;

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses;

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure;

CAS = Chemical Abstracts Service;

CERCLA = Comprehensive Environmental Response, Compensation and Liability Act;

CFR = Code of Federal Regulations;

CPR = Controlled Products Regulations;

DMEL = Derived Minimum Effect Level;

DNEL = Derived No Effect Level;

DOT = Department of Transportation;

EC50 = Median effective concentration;

EPA = Environmental Protection Agency;

GHS = Globally Harmonized System of Classification and Labelling of Chemicals;

IATA = International Air Transport Association;

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk;

IC50 = Inhibition concentration, 50%;

IMDG = International Maritime Code for Dangerous Goods;

IARC = International Agency of Research on Cancer;

IATA = International Air Transport Association;

TSCA = Toxic Substance Control Act;

HMIS = Hazardous Materials Identification System;

NFPA = National Fire Protection Association;

NIOSH = National Institute for Occupational Safety and Health;

OSHA = Occupational Safety and Health Administration;

LC50 = Lethal concentration, 50%;

LD50 = Median lethal dose, 50%;

MARPOL = International Convention for the Prevention of Marine Pollution from Ships;

PBT = Persistent, Bioaccumulative and Toxic substance;

PNEC = Predicted No-Effect Concentration;

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals;

SARA = Superfund Amendments and Reauthorization Act;

TLV®/TWA = Threshold limit value – time-weighted average; TLV®STEL = Threshold limit value – short-time exposure limit;

VOC = Volatile Organic Compounds;

vPvB = very Persistent and very Bioaccumulative;

16.2 Ratings

Gear oil 75W - 90 Article number 32590



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.04.2024, Revision 02.04.2024

Version 12.0. Supersedes version: 10.0 Page 14 / 14

NFPA Ratings



TOP, FLAMMABILITY: 1 - Slight Hazard LEFT, HEALTH: 1 - Slight Hazard RIGHT, REACTIVITY: 1 - Slight Hazard BOTTOM, SPECIAL NOTICE:

HMIS Ratings



- 1 Slight Hazard
- 1 Slight Hazard
- 1 Slight Hazard
- X Personal protection rating to be supplied by user depending on use conditions

PERSONAL PROTECTION:

- A Safety Glasses
- B Safety Glasses and Gloves
- C Safety Glasses, Gloves and Protection Apron
- D Face Shield, Gloves and Protection Apron
- E Safety Glasses, Gloves and Dust Respirator
- F Safety Glasses, Gloves, Protection Apron and Dust Respirator
- G Safety Glasses, Gloves and Vapor Respirator.
- H Splash Goggles, Gloves, Protection Apron and Vapor Respirator.
- I Safety Glasses, Gloves, Dust Respirator and Vapor Respirator.
- J Splash Goggles, Gloves, Protection Apron, Dust Respirator and Vapor Respirator.
- K Airline Mask or Hood, Gloves, Full Suit and Boots.
- X Personal protection rating to be supplied by user depending on use conditions

Modified position

None

bfe00077