

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 1 / 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Enginr oil 10W - 40
Article number: 32931, 32932, 32933, 32934, 32935, 72931, 72935

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Engine oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG
Wilhelmstr. 47
58256 Ennepetal / GERMANY
Phone +49 2333 911-0
Fax +49 2333 911-444
Homepage www.febi.com
E-mail info@febi.com

Address enquiries to

Technical information info@febi.com

Safety Data Sheet sdb@chemiebuero.de (No dispatch of safety data sheets)
Safety data sheets are available from the supplier.

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

The product is classified as hazardous in accordance to OSHA Standard 29 CFR 1910.1200 (HCS 2012)

Hazard pictograms

Hazard statements H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P273 Avoid release to the environment.
P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

2.3 Other hazards

Human health dangers Frequent persistent contact with the skin can cause skin irritation.

Environmental hazards Contains no ingredients with endocrine-disrupting properties ($\geq 0,1\%$).
This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Other hazards No particular hazards known.

This product is classified as non-hazardous in accordance to OSHA Standard 29 CFR 1910.1200.

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 2 / 15

SECTION 3: Composition / Information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
1 - < 2,5	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
1 - < 2,5	Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt) CAS: 64742-65-0
<0,1	phenol, (tetrapropenyl) derivatives CAS: 74499-35-7

Comment on component parts

For full text of H-statements: see SECTION 16.
All chemical substances in this material are included on or exempted from listing on the IECSC Inventory.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Take off contaminated clothing and wash before reuse.

Inhalation

Ensure supply of fresh air.
In the event of symptoms seek medical treatment.

Skin contact

In case of contact with skin wash off immediately with soap and water.
Consult a doctor if skin irritation persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion

Consult a doctor immediately.
Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Fire extinguishing method of surrounding areas must be considered.
Foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not be used

Full water jet

5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.
Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 3 / 15

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.
Ensure adequate ventilation.
Use personal protective equipment (protective gloves, safety glasses, protective clothing).

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.
Do not smoke.
Fire class (DIN EN 2): B
Do not eat, drink or smoke when using this product.
Use barrier skin cream.
Wash hands before breaks and after work.
Cloths contaminated with product should not be kept in trouser pockets.
Contaminated work clothing should not be allowed out of the workplace.
Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Keep container tightly closed.
Keep container in a well-ventilated place.

7.3 Specific end use(s)

See product use, SECTION 1.2



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 4 / 15

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (US)

Not applicable

DNEL

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5,58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, oral, Long-term - local effects, 740 µg/kg bw/day
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
Industrial, inhalative, Long-term - systemic effects, 3,5 mg/m ³
Industrial, inhalative, Acute - systemic effects, 133,6 mg/m ³
Industrial, dermal, Long-term - systemic effects, 8,33 mg/kg bw/day
Industrial, dermal, Acute - systemic effects, 80 mg/kg bw/day
general population, dermal, Long-term - systemic effects, 4,2 mg/kg bw/day
general population, dermal, Acute - systemic effects, 40 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0,25 mg/kg bw/day
general population, oral, Acute - systemic effects, 50 mg/kg bw/day
general population, inhalative, Long-term - systemic effects, 0,87 mg/m ³
general population, inhalative, Acute - systemic effects, 0,067 mg/m ³

PNEC

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
oral (food), 9,33 mg/kg food
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
freshwater, 0,5 mg/l
sediment (seawater), 0,05 mg/L
sewage treatment plants (STP), 100 mg/l
sediment (freshwater), 1650 mg/kg
sediment (seawater), 165 mg/kg
soil, 8850 mg/kg
oral (food), 13333 mg/kg

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 5 / 15

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances. General limit for oil mist should be noted.
Eye protection	If there is a risk of splashing: safety glasses
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,4 mm; Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	light protective clothing
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection. Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)
Thermal hazards	None
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 6 / 15

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Form	Liquid
Color	brown
Odor	characteristic
Odor threshold	Not applicable
pH-value	Not applicable
pH-value [1%]	Not applicable
Boiling point or initial boiling point and boiling range [°C]	No information available.
Flash point [°C]	>200 (ISO 2592)
Flammability	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidizing properties	No
Vapor pressure/gas pressure [kPa]	<0,01 (20°C)
Density [g/cm ³]	0,86 (DIN 51757) (15 °C / 59,0 °F)
Relative density	Not determined
Bulk density [kg/m ³]	Not applicable
Solubility in water	immiscible
Solubility other solvents	No information available.
Partition coefficient n-octanol/water (log value)	No information available.
Kinematic viscosity	>20,5 mm ² /s (40° C) 14,2 mm ² /s (100°C) (DIN 51562/T1)
Relative vapour density	No information available.
Melting point [°C]	No information available.
Auto-ignition temperature [°C]	No information available.
Decomposition temperature [°C]	No information available.
Particle characteristics	No information available.

9.2 Other information

Pour point: ca. -33°C (DIN ISO 3016)

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating.



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 7 / 15

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

In the case of heating following (decomposition) products may occur:
>65°C / Hydrogen sulfide ((H₂S)).

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 8 / 15

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity Based on available data, the classification criteria are not met.

Product
ATE-mix, oral, >2000 mg/kg bw
Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, oral, Rat, 5000 mg/kg bw
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
LD50, oral, Rat, >5000 mg/kg bw
phenol, (tetrapropenyl) derivatives, CAS: 74499-35-7
LD50, oral, Rat, 2200 mg/kg bw, OECD 401

Acute dermal toxicity Based on available data, the classification criteria are not met.

Product
ATE-mix, dermal, >2000 mg/kg bw
Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, dermal, Rabbit, > 2000 - 5000 mg/kg bw
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
LD50, dermal, Rabbit, >4000 mg/kg bw
phenol, (tetrapropenyl) derivatives, CAS: 74499-35-7
LD50, dermal, Rabbit, 15000 mg/kg bw, OECD 402

Acute inhalational toxicity Based on available data, the classification criteria are not met.

Product
ATE-mix, inhalativ (vapor), >20 mg/L
Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LC50, inhalative, Rat, 2,18 - 5,53 mg/L air 4h, 4h
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
LC50, inhalative, Rat, >1,67 mg/l

Serious eye damage/irritation Based on the information available, the classification criteria have not been fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Eye, non-irritating
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
Eye, Rabbit, OECD 405, non-irritating

Skin corrosion/irritation Based on the information available, the classification criteria have not been fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-irritating

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 9 / 15

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
dermal, Rabbit, OECD 404, non-irritating

Respiratory or skin sensitisation Based on the information available, the classification criteria have not been fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-sensitizing
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
dermal, Human, In vivo study, non-sensitizing

Specific target organ toxicity — single exposure Based on the information available, the classification criteria have not been fulfilled.

Specific target organ toxicity — repeated exposure Based on the information available, the classification criteria have not been fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOAEL, inhalative, Rat, 980 mg/m ³ air, no adverse effect observed
LOAEL, dermal, mouse, 100 mg/kg bw/day, The effects observed are not sufficient for classification.
LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
NOAEL, oral, Rat, 1000 mg/kg bw/day, no adverse effect observed
NOAEL, dermal, Rat, 250 mg/kg bw/day, no adverse effect observed

Mutagenicity Based on the information available, the classification criteria have not been fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
in vitro, negativ
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
in vitro, OECD 471, negativ

Reproduction toxicity Based on the information available, the classification criteria have not been fulfilled.

- Fertility

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
NOAEL, oral, Rat, 300 mg/kg bw/day, OECD 416, adverse effect observed

- Development

Substance
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
NOAEL, oral, Rat, 50 mg/kg bw/day, OECD 416, adverse effect observed, Effect on developmental toxicity,

Carcinogenicity Based on the information available, the classification criteria have not been fulfilled.

Aspiration hazard Based on the information available, the classification criteria have not been fulfilled.
On basis of test data

General remarks Frequent persistent contact with the skin can cause skin irritation.
Toxicological data of complete product are not available.

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 10 / 15

SECTION 12: Ecological information

12.1 Toxicity

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOELR, (14d), fish, 1 g/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), fish, 100 mg/L
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
LC50, (3d), Invertebrates, 40 mg/L
EL50, (3d), Algae, 500 mg/L
LL50, (3d), fish, 1 - 10 g/L

12.2 Persistence and degradability

Behaviour in environment compartments	Not determined
Behaviour in sewage plant	Not determined
Biological degradability	Not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Ecological data of complete product are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

In according to RoHS!
Coordinate disposal with the disposal contractor/authorities if necessary.
Dispose of as hazardous waste.

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

RCRA Hazard Class (40CFR 261)

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities.

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 11 / 15

SECTION 14: Transport

14.1 UN number

Transport by land according to ADR/RID Not applicable

Inland navigation (ADN) Not applicable

Marine transport in accordance with IMDG Not applicable

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 CFR) Not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

DOT Road Shipment Information (49 CFR) NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID Not applicable

Inland navigation (ADN) Not applicable

Marine transport in accordance with IMDG Not applicable

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 CFR) Not applicable

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 12 / 15

14.4 Packing group

Transport by land according to ADR/RID Not applicable

Inland navigation (ADN) Not applicable

Marine transport in accordance with IMDG Not applicable

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 CFR) Not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID No

Inland navigation (ADN) No

Marine transport in accordance with IMDG No

Air transport in accordance with IATA No

DOT Road Shipment Information (49 CFR) No

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 13 / 15

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

US Regulations

National regulations

29 CFR 1910.1200-HCS 2012, OSHA-PEL, ACGIH-TLV, NTP, IARC, SARA Title III, NFPA, TSCA, California - Prop. 65

- SARA, 302

This product does not contain any ingredients regulated under this list.

- SARA, 311

This product does not contain any ingredients regulated under this list.

- SARA, 313

This product does not contain any ingredients regulated under this list.

- CA Proposition 65

No components require labeling under California Proposition 65.

- TSCA

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory.

- FDA

Not applicable

American Conference of Governmental Industrial Hygienists - ACGIH

Ingredients not listed as carcinogens.

International Agency for Research on Cancer IARC

Ingredients not listed as carcinogens.

National Toxicology Program - NTP

Ingredients not listed.

HAP-VOC

This product does not contain HAP's ore VOC.

Transport-regulations

DOT-Classification, ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)

15.2 Chemical safety assessment

Not applicable

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 14 / 15

SECTION 16: Other information

16.1 Abbreviations and acronyms:

ACGIH = American Conference of Governmental Industrial Hygienists;
ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route;
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses;
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure;
CAS = Chemical Abstracts Service;
CERCLA = Comprehensive Environmental Response, Compensation and Liability Act;
CFR = Code of Federal Regulations;
CPR = Controlled Products Regulations;
DMEL = Derived Minimum Effect Level;
DNEL = Derived No Effect Level;
DOT = Department of Transportation;
EC50 = Median effective concentration;
EPA = Environmental Protection Agency;
GHS = Globally Harmonized System of Classification and Labelling of Chemicals;
IATA = International Air Transport Association;
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk;
IC50 = Inhibition concentration, 50%;
IMDG = International Maritime Code for Dangerous Goods;
IARC = International Agency of Research on Cancer;
IATA = International Air Transport Association;
TSCA = Toxic Substance Control Act;
HMIS = Hazardous Materials Identification System;
NFPA = National Fire Protection Association;
NIOSH = National Institute for Occupational Safety and Health;
OSHA = Occupational Safety and Health Administration;
LC50 = Lethal concentration, 50%;
LD50 = Median lethal dose, 50%;
MARPOL = International Convention for the Prevention of Marine Pollution from Ships;
PBT = Persistent, Bioaccumulative and Toxic substance;
PNEC = Predicted No-Effect Concentration;
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals;
SARA = Superfund Amendments and Reauthorization Act;
TLV@/TWA = Threshold limit value – time-weighted average;
TLV@STEL = Threshold limit value – short-time exposure limit;
VOC = Volatile Organic Compounds;
vPvB = very Persistent and very Bioaccumulative;

16.2 Ratings

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.02.2024, Revision 21.02.2024

Version 11.0. Supersedes version: 9.0

Page 15 / 15

NFPA Ratings



TOP, FLAMMABILITY: 1 - Slight Hazard
LEFT, HEALTH: 2 - Moderate Hazard
RIGHT, REACTIVITY: 0 - Minimal Hazard
BOTTOM, SPECIAL NOTICE: 20.NFPA.X0

HMIS Ratings

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

2 - Moderate Hazard
1 - Slight Hazard
0 - Minimal Hazard
X - Personal protection rating to be supplied by user depending on use conditions

PERSONAL PROTECTION:

- A - Safety Glasses
- B - Safety Glasses and Gloves
- C - Safety Glasses, Gloves and Protection Apron
- D - Face Shield, Gloves and Protection Apron
- E - Safety Glasses, Gloves and Dust Respirator
- F - Safety Glasses, Gloves, Protection Apron and Dust Respirator
- G - Safety Glasses, Gloves and Vapor Respirator.
- H - Splash Goggles, Gloves, Protection Apron and Vapor Respirator.
- I - Safety Glasses, Gloves, Dust Respirator and Vapor Respirator.
- J - Splash Goggles, Gloves, Protection Apron, Dust Respirator and Vapor Respirator.
- K - Airline Mask or Hood, Gloves, Full Suit and Boots.
- X - Personal protection rating to be supplied by user depending on use conditions

Modified position

1.3, 2.2, 3.2, 5.1, 6.1, 7.1, 8.1, 8.2, 9.1, 9.2, 11.1, 11.2, 12.6, 12.7, 15.1, 16.2, 16.3