Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

Page 1 / 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Engine Oil 5W - 40

Article number: 32936, 32937, 32938, 32939, 32940, 72936, 72938,

72939, 77940

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Engine oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

The product is classified as hazardous in accordance to OSHA Standard 29 CFR 1910.1200

(HCS 2012)

Hazard pictograms None
Signal word None

Hazard statements H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P102 Keep out of reach of children.

P273 Avoid release to the environment.

P501 Dispose of contents/container to in accordance with local/regional/national/international

regulation.

2.3 Other hazards

Human health dangers Frequent persistent contact with the skin can cause skin irritation.

If swallowed or in the event of vomiting, risk of product entering the lungs.

Environmental hazardsDoes not contain any PBT or vPvB substances.

Contains no ingredients with endocrine-disrupting properties.

Other hazards Further hazards were not determined with the current level of knowledge.

This product is classified as hazardous in accordance to OSHA Standard 29 CFR 1910.1200.

Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

Page 2 / 15

SECTION 3: Composition / Information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
30 - < 60	Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-54-7
<2,5	Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt)
	CAS: 64742-65-0
<2,5	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
<0,1	phenol, (tetrapropenyl) derivatives
	CAS: 74499-35-7

Comment on component parts For full text of H-statements: see SECTION 16.

All chemical substances in this material are included on or exempted from listing on the

IECSC Inventory.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Take off contaminated clothing and wash before reuse.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contactRinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Consult a doctor immediately.

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Fire extinguishing method of surrounding areas must be considered.

Foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not

be used

Full water jet

5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.

Risk of formation of toxic pyrolysis products.

Phosphorus oxides (POx). Sulphur oxides (SOx). Nitrogen oxides (NOx).

Engine Oil 5W - 40



Page 3 / 15

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Forms slippery surfaces with water.

Use personal protective equipment (protective gloves, safety glasses, protective clothing).

Ensure adequate ventilation.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder). Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.

Do not smoke.

Fire class (DIN EN 2): B

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Wash hands before breaks and after work.

Cloths contaminated with product should not be kept in trouser pockets.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Keep container tightly closed. Protect from heat/overheating.

7.3 Specific end use(s)

See product use, SECTION 1.2

Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

Page 4 / 15

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (US)

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)

CAS: 64742-54-7

Long-term exposure: 5 mg/m³, OSHA, oil mist

DNEL

Substance		
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7		
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³		
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³		
Industrial, dermal, Long-term - systemic effects, 970 μg/kg bw/day		
general population, inhalative, Long-term - local effects, 1.19 mg/m³		
general population, oral, Long-term - systemic effects, 740 μg/kg bw/day		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0		
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m³		
Industrial, inhalative, Long-term - local effects, 5,58 mg/m³		
Industrial, dermal, Long-term - systemic effects, 970 μg/kg bw/day		
general population, oral, Long-term - local effects, 740 μg/kg bw/day		
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased		
Industrial, inhalative, Long-term - systemic effects, 3,5 mg/m³		
Industrial, inhalative, Acute - systemic effects, 133,6 mg/m³		
Industrial, dermal, Long-term - systemic effects, 8,33 mg/kg bw/day		
Industrial, dermal, Acute - systemic effects, 80 mg/kg bw/day		
general population, dermal, Long-term - systemic effects, 4,2 mg/kg bw/day		
general population, dermal, Acute - systemic effects, 40 mg/kg bw/day		
general population, oral, Long-term - systemic effects, 0,25 mg/kg bw/day		
general population, oral, Acute - systemic effects, 50 mg/kg bw/day		
general population, inhalative, Long-term - systemic effects, 0,87 mg/m³		
general population, inhalative, Acute - systemic effects, 0,067 mg/m³		

PNEC

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7		
oral (food), 9,33 mg/kg		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0		
oral (food), 9,33 mg/kg food		
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased		
freshwater, 0,5 mg/l		
sediment (seawater), 0,05 mg/L		
sewage treatment plants (STP), 100 mg/l		
sediment (freshwater), 1650 mg/kg		
sediment (seawater), 165 mg/kg		
soil, 8850 mg/kg		
oral (food), 13333 mg/kg		

Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

Page 5 / 15

8.2 Exposure controls

Additional advice on system design
Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

General limit for oil mist should be noted.

Eye protection If there is a risk of splashing:

safety glasses

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

>0,11 mm; Nitrile rubber, >480 min (EN 374-1/-2/-3).

Skin protection light protective clothing

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

Respiratory protection In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear

appropriate respiratory protection.

Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)

Thermal hazards None

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

Page 6 / 15

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical stateLiquidFormLiquidColorbrownOdorcharacteristicOdor thresholdNot applicablepH-valueNot applicablepH-value [1%]Not applicable

Boiling point or initial boiling point

and boiling range [°C]

No information available.

Flash point [°C] >200 (ISO 2592)

Flammability No information available.

Lower explosion limit No information available.

Upper explosion limit No information available.

Oxidizing properties No

Vapor pressure/gas pressure [kPa] <0,01 (20°C)

Density [g/cm³] 0,85 (DIN 51757) (15 °C / 59,0 °F)

Relative density

Bulk density [kg/m³]

Not applicable

Solubility in water

Not applicable

Solubility other solvents No information available.

Partition coefficient n-octanol/water No information available.

(log value)

Kinematic viscosity

88,6 mm²/s (40°C) (DIN 51562/T1)

Relative vapour density

Melting point [°C]

Auto-ignition temperature [°C]

Decomposition temperature [°C]

Particle characteristics

No information available.

No information available.

No information available.

9.2 Other information

Pour point: ca. -33 (ISO 3016)

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating.

Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

Page 7 / 15

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

In the case of heating following (decomposition) products may occure: Hydrogen sulfide ((H2S).

Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

Page 8 / 15

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity

Based on available data, the classification criteria are not met.

Product

ATE-mix, oral, >2000 mg/kg bw

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LD50, oral, Rat, 5000 mg/kg bw

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

LD50, oral, Rat, 5000 mg/kg bw

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased

LD50, oral, Rat, >5000 mg/kg bw

phenol, (tetrapropenyl) derivatives, CAS: 74499-35-7

LD50, oral, Rat, 2200 mg/kg bw, OECD 401

Acute dermal toxicity

Based on available data, the classification criteria are not met.

Product

ATE-mix, dermal, >2000 mg/kg bw

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LD50, dermal, Rabbit, 2000 - 5 00 mg/kg bw

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

LD50, dermal, Rabbit, > 2000 - 5000 mg/kg bw

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased

LD50, dermal, Rabbit, >4000 mg/kg bw

phenol, (tetrapropenyl) derivatives, CAS: 74499-35-7

LD50, dermal, Rabbit, 15000 mg/kg bw, OECD 402

Acute inhalational toxicity

Based on available data, the classification criteria are not met.

Product

ATE-mix, inhalativ (vapor), >20 mg/L

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

LC50, inhalative, Rat, 2,18 - 5,53 mg/L air 4h, 4h

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased

LC50, inhalative, Rat, >1,67 mg/l

Serious eye damage/irritation

Based on the information available, the classification criteria have not been fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

Eye, non-irritating

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased

Engine Oil 5W - 40



Page 9 / 15

Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

Eye, Rabbit, OECD 405, non-irritating

Skin corrosion/irritation

Based on the information available, the classification criteria have not been fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

dermal, non-irritating

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased

dermal, Rabbit, OECD 404, non-irritating

Respiratory or skin sensitisation

Based on the information available, the classification criteria have not been fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

dermal, non-sensitizing

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased

dermal, Human, In vivo study, non-sensitizing

Specific target organ toxicity — single exposure

Based on the information available, the classification criteria have not been fulfilled.

Specific target organ toxicity — repeated exposure

Based on the information available, the classification criteria have not been fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day

NOAEL, dermal, Rabbit, 1000 mg/kg bw/day

NOAEC, inhalative, Rat, 980 mg/m³ air

LOAEL, oral, Rat, 125 mg/kg bw/day

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOAEL, inhalative, Rat, 980 mg/m³ air, no adverse effect observed

LOAEL, dermal, mouse, 100 mg/kg bw/day, The effects observed are not sufficient for classification.

LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased

NOAEL, oral, Rat, 1000 mg/kg bw/day, no adverse effect observed

NOAEL, dermal, Rat, 250 mg/kg bw/day, no adverse effect observed

Mutagenicity

Based on the information available, the classification criteria have not been fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

in vitro, negativ

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased

in vitro, OECD 471, negativ

Reproduction toxicity

Based on the information available, the classification criteria have not been fulfilled.

- Fertility

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed

Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0 Pa

Page 10 / 15

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased

NOAEL, oral, Rat, 300 mg/kg bw/day, OECD 416, adverse effect observed

- Development

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased

NOAEL, oral, Rat, 50 mg/kg bw/day, OECD 416, adverse effect observed, Effect on developmental toxicity,

CarcinogenicityBased on the information available, the classification criteria have not been fulfilled.Aspiration hazardBased on the information available, the classification criteria have not been fulfilled.

General remarks

Toxicological data of complete product are not available.

SECTION 12: Ecological information

12.1 Toxicity

Substance		
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7		
EL50, (48h), Invertebrates, 10 g/L		
NOELR, (14d), fish, 1 mg/L		
LL50, (96h), Invertebrates, 10 g/L		
LL50, (96h), fish, 100 mg/L		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0		
NOELR, (14d), fish, 1 g/L		
LL50, (96h), Invertebrates, 10 g/L		
LL50, (96h), fish, 100 mg/L		
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased		
LC50, (3d), Invertebrates, 40 mg/L		
EL50, (3d), Algae, 500 mg/L		
LL50, (3d), fish, 1 - 10 g/L		

12.2 Persistence and degradability

Behaviour in environment

Not determined

compartments

Can be separated out mechanically in purification plants.

Behaviour in sewage plant Biological degradability

The product is only slightly biodegradable.

Slightly eliminable from water.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

Page 11 / 15

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Ecological data of complete product are not available. Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

In according to RoHS!

Coordinate disposal with the disposal contractor/authorities if necessary.

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

RCRA Hazard Class (40CFR 261)

No information available.

SECTION 14: Transport

14.1 UN number

Transport by land according to

ADR/RID

Not applicable

Inland navigation (ADN)

Not applicable

Marine transport in accordance with

IMDG

Not applicable

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 Not applicable

CFR)

14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

IMDG

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

DOT Road Shipment Information (49 Not applicable

CFR)

Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

Page 12 / 15

14.3 Transport hazard class(es)

Transport by land according to ADR/RID

Not applicable

Inland navigation (ADN)

Not applicable

Marine transport in accordance with **IMDG**

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 Not applicable

CFR)

14.4 Packing group

Transport by land according to ADR/RID

Not applicable

Inland navigation (ADN)

Not applicable

Marine transport in accordance with Not applicable

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 Not applicable

CFR)

14.5 Environmental hazards

Transport by land according to

ADR/RID

No

Inland navigation (ADN)

No

Marine transport in accordance with No

IMDG

Air transport in accordance with IATA No

DOT Road Shipment Information (49 No

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

Page 13 / 15

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

US Regulations

National regulations 29 CFR 1910.1200-HCS 2012, OSHA-PEL, ACGIH-TLV, NTP, IARC, SARA Title III, NFPA,

TSCA, California - Prop. 65

SARA, 302 No information available.
 SARA, 311 No information available.
 SARA, 313 No information available.

- CA Proposition 65 No components require labeling under California Proposition 65.

- TSCA All chemical substances in this material are included on or exempted from listing on the TSCA

Inventory.

- FDA

American Conference of

No information available.

Governmental Industrial Hygienists -

ACGIH

International Agency for Research on No information available.

Cancer IARC

National Toxicology Program - NTP No information available.

HAP-VOC

Transport-regulations DOT-Classification, ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)

15.2 Chemical safety assessment

For this product a chemical safety assessment has not been carried out.

Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0

Page 14 / 15

SECTION 16: Other information

16.1 Abbreviations and acronyms:

ACGIH = American Conference of Governmental Industrial Hygienists;

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route;

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses;

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure;

CAS = Chemical Abstracts Service;

CERCLA = Comprehensive Environmental Response, Compensation and Liability Act;

CFR = Code of Federal Regulations;

CPR = Controlled Products Regulations;

DMEL = Derived Minimum Effect Level;

DNEL = Derived No Effect Level;

DOT = Department of Transportation;

EC50 = Median effective concentration;

EPA = Environmental Protection Agency;

GHS = Globally Harmonized System of Classification and Labelling of Chemicals;

IATA = International Air Transport Association;

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk;

IC50 = Inhibition concentration, 50%;

IMDG = International Maritime Code for Dangerous Goods;

IARC = International Agency of Research on Cancer;

IATA = International Air Transport Association;

TSCA = Toxic Substance Control Act;

HMIS = Hazardous Materials Identification System;

NFPA = National Fire Protection Association;

NIOSH = National Institute for Occupational Safety and Health;

OSHA = Occupational Safety and Health Administration;

LC50 = Lethal concentration, 50%;

LD50 = Median lethal dose, 50%;

MARPOL = International Convention for the Prevention of Marine Pollution from Ships;

PBT = Persistent, Bioaccumulative and Toxic substance;

PNEC = Predicted No-Effect Concentration;

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals;

SARA = Superfund Amendments and Reauthorization Act;

TLV®/TWA = Threshold limit value – time-weighted average; TLV®STEL = Threshold limit value – short-time exposure limit;

VOC = Volatile Organic Compounds;

vPvB = very Persistent and very Bioaccumulative;

16.2 Ratings

Engine Oil 5W - 40



Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 14.0. Supersedes version: 11.0 Page 15 / 15

NFPA Ratings



TOP, FLAMMABILITY: 1 - Slight Hazard LEFT, HEALTH: 0 - Minimal Hazard RIGHT, REACTIVITY: 0 - Minimal Hazard BOTTOM, SPECIAL NOTICE:

HMIS Ratings



- 0 Minimal Hazard
- 1 Slight Hazard
- 0 Minimal Hazard
- X Personal protection rating to be supplied by user depending on use conditions

PERSONAL PROTECTION:

- A Safety Glasses
- B Safety Glasses and Gloves
- C Safety Glasses, Gloves and Protection Apron
- D Face Shield, Gloves and Protection Apron
- E Safety Glasses, Gloves and Dust Respirator
- F Safety Glasses, Gloves, Protection Apron and Dust Respirator
- G Safety Glasses, Gloves and Vapor Respirator.
- H Splash Goggles, Gloves, Protection Apron and Vapor Respirator.
- I Safety Glasses, Gloves, Dust Respirator and Vapor Respirator.
- J Splash Goggles, Gloves, Protection Apron, Dust Respirator and Vapor Respirator.
- K Airline Mask or Hood, Gloves, Full Suit and Boots.
- X Personal protection rating to be supplied by user depending on use conditions

Modified position

 $1.3,\, 2.1,\, 2.2,\, 2.3,\, 3.2,\, 5.1,\, 6.1,\, 8.1,\, 8.2,\, 9.1,\, 9.2,\, 11.1,\, 11.2,\, 12.6,\, 12.7,\, 15.1,\, 16.2,\, 16.3$