

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Engine Oil 5W - 30 Longlife****Article number: 32941, 32942, 32943, 32944, 39336, 77941, 72943, 79336****1.2 Relevant identified uses of the substance or mixture and uses advised against****1.2.1 Relevant uses**

Engine oil

1.2.2 Uses advised against

For all uses not specified in SECTION 1.2.1

1.3 Details of the supplier of the safety data sheet**Company**

Ferdinand Bilstein GmbH + Co. KG
 Wilhelmstr. 47
 58256 Ennepetal / GERMANY
 Phone +49 2333 911-0
 Fax +49 2333 911-444
 Homepage www.febi.com
 E-mail info@febi.com

Address enquiries to**Technical information**info@febi.com**Safety Data Sheet**info@febi.com**1.4 Emergency telephone number****Advisory body**

+49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture [REGULATION (GB) CLP]**

No classification.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms

none

Signal word

none

Hazard statements

none

Precautionary statements

none

Special labelling

EUH210 Safety data sheet available on request.

Contains: Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated. EUH208 May produce an allergic reaction.

2.3 Other hazards**Physico-chemical hazards**

No particular hazards known.

Human health dangers

If swallowed or in the event of vomiting, risk of product entering the lungs.
 Frequent persistent contact with the skin can cause skin irritation.

Environmental hazards

Does not contain any PBT or vPvB substances.
 Contains no ingredients with endocrine-disrupting properties.

Other hazards

Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients**3.1 Substances**

not applicable

Ferdinand Bilstein GmbH + Co. KG

Date printed 26.02.2024, Revision 26.02.2024

Version 11.0. Supersedes version: 10.0

Page 2 / 11

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
30 - < 60	Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
	GHS/CLP: Asp. Tox. 1: H304
0,3 - < 1	Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated
	CAS: -, EINECS/ELINCS: 953-650-0
	GHS/CLP: Skin Sens. 1B: H317 - Repr. 2: H361d
	SCL [%]: 17,15 - 100: Repr. 2: H361

Comment on component parts All chemical substances in this material are included on or exempted from listing on the IECSC Inventory.
For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Change soaked clothing.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.
Skin contact	In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Consult a doctor immediately. Rinse out mouth and give plenty of water to drink. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If swallowed or in the event of vomiting, risk of product entering the lungs.
Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Fire extinguishing method of surrounding areas must be considered. Foam, dry powder, water spray jet, carbon dioxide
Extinguishing media that must not be used	Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)
Sulphur oxides (SO_x).
Nitrogen oxides (NO_x).
Hydrogen sulfide ((H₂S).

Ferdinand Bilstein GmbH + Co. KG

Date printed 26.02.2024, Revision 26.02.2024

Version 11.0. Supersedes version: 10.0

Page 3 / 11

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.
Ensure adequate ventilation.
Use personal protective equipment (protective gloves, safety glasses, protective clothing).

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.
Do not smoke.
Fire class (DIN EN 2): B
Wash hands before breaks and after work.
Do not eat, drink or smoke when using this product.
Use barrier skin cream.
Take off contaminated clothing and wash before reuse.
Cloths contaminated with product should not be kept in trouser pockets.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Do not store together with food and animal food/diet.
Keep container tightly closed.
Protect from heat/overheating.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (UK)

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
Long-term exposure: 5 mg/m ³ , oil mist
Short-term exposure (15-minute): 10 mg/m ³

Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

DNEL

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5.58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, inhalative, Long-term - local effects, 1.19 mg/m ³
general population, oral, Long-term - systemic effects, 740 µg/kg bw/day
Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated, CAS: -
There are no DNEL values established for the substance.

PNEC

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
oral (food), 9,33 mg/kg
Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated, CAS: -
There are no PNEC values established for the substance.

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. >0,11 mm: Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	Light protective clothing.
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection. Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	liquid
Color	brown
Odor	characteristic
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	No information available.
Boiling point or initial boiling point and boiling range [°C]	No information available.
Flash point [°C]	>230 (ISO 2592)
Flammability	not applicable
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	<0,01 (20°C)
Density [g/cm ³]	ca. 0,851 (DIN 51757) (15 °C / 59,0 °F)
Relative density	not determined
Bulk density [kg/m ³]	not applicable
Solubility in water	virtually insoluble
Solubility other solvents	No information available.
Partition coefficient n-octanol/water (log value)	No information available.
Kinematic viscosity	ca. 12,2 mm ² /s (100°C) (DIN 51562/T1) >20,5 mm ² /s (40°C)
Relative vapour density	No information available.
Melting point [°C]	No information available.
Auto-ignition temperature [°C]	No information available.
Decomposition temperature [°C]	No information available.
Particle characteristics	No information available.

9.2 Other information

Pour point: <-30 (DIN ISO 3016)

SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong acids.

Strong heating, because the thermal decomposition starts from > 65°C.



Ferdinand Bilstein GmbH + Co. KG

Date printed 26.02.2024, Revision 26.02.2024

Version 11.0. Supersedes version: 10.0

Page 6 / 11

10.5 Incompatible materials

- Oxidizing agent
- Acids
- Strong basic compounds

10.6 Hazardous decomposition products

In the case of heating following (decomposition) products may occur:
Hydrogen sulfide (H₂S).

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity** Based on available data, the classification criteria are not met.

Product
ATE-mix, oral, >2000 mg/kg bw
Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LD50, oral, Rat, 5000 mg/kg bw

Acute dermal toxicity Based on available data, the classification criteria are not met.

Product
ATE-mix, dermal, >2000 mg/kg bw
Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LD50, dermal, Rabbit, 2000 - 5 00 mg/kg bw

Acute inhalational toxicity Based on available data, the classification criteria are not met.

Product
ATE-mix, inhalation (vapour), >20 mg/L
Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Serious eye damage/irritation Based on the available information, the classification criteria are not fulfilled.**Skin corrosion/irritation** Based on the available information, the classification criteria are not fulfilled.**Respiratory or skin sensitisation** May produce an allergic reaction.**Specific target organ toxicity — single exposure** Based on the available information, the classification criteria are not fulfilled.**Specific target organ toxicity — repeated exposure** Based on the available information, the classification criteria are not fulfilled.

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day
NOAEL, dermal, Rabbit, 1000 mg/kg bw/day
NOAEC, inhalative, Rat, 980 mg/m ³ air
LOAEL, oral, Rat, 125 mg/kg bw/day

Mutagenicity Based on the available information, the classification criteria are not fulfilled.**Reproduction toxicity** Based on the available information, the classification criteria are not fulfilled.**- Fertility**

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

- Development

Ferdinand Bilstein GmbH + Co. KG

Date printed 26.02.2024, Revision 26.02.2024

Version 11.0. Supersedes version: 10.0

Page 8 / 11

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

Carcinogenicity Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard Based on the available information, the classification criteria are not fulfilled.
General remarks

Toxicological data of complete product are not available.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties Contains no ingredients with endocrine-disrupting properties.

11.2.2 Other information none

SECTION 12: Ecological information**12.1 Toxicity**

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
EL50, (48h), Invertebrates, 10 g/L
NOELR, (14d), fish, 1 mg/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), fish, 100 mg/L

12.2 Persistence and degradability

Behaviour in environment compartments

Behaviour in sewage plant

Biological degradability The product is not readily biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the authorities if necessary.
 Disposal in an incineration plant in accordance with the regulations of the local authorities.
 In according to RoHS!

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
 Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

Ferdinand Bilstein GmbH + Co. KG

Date printed 26.02.2024, Revision 26.02.2024

Version 11.0. Supersedes version: 10.0

Page 10 / 11

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

EEC-REGULATIONS 2008/98/EG (2000/532/EG); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EG) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EWG ((EG) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021

- **Comment on component parts** Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

- **Annex I (REACH)** The product is not subject to Annex I restrictions.

- **Annex XIV (REACH)** According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain any substances \geq 0.1% that are subject to authorisation.

- **Annex XVII (REACH)** According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product contains \geq 0.1% of substances with the following restrictions. 75

According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is not subject to any restrictions.

TRANSPORT-REGULATIONS ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)

NATIONAL REGULATIONS (UK): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.

- **Observe employment restrictions for people** no

- **VOC (2010/75/CE)** not relevant

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H304 May be fatal if swallowed and enters airways.
 H361d Suspected of damaging the unborn child.
 H317 May cause an allergic skin reaction.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 ATE = acute toxicity estimate
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging
 DMEL = Derived Minimum Effect Level
 DNEL = Derived No Effect Level
 EC50 = Median effective concentration
 ECB = European Chemicals Bureau
 EEC = European Economic Community
 EINECS = European Inventory of Existing Commercial Chemical Substances
 EL50 = Median effective loading
 ELINCS = European List of Notified Chemical Substances
 EmS = Emergency Schedules
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IC50 = Inhibition concentration, 50%
 IMDG = International Maritime Code for Dangerous Goods
 IUCLID = International Uniform Chemical Information Database
 IVIS = In vitro irritation score
 LC50 = Lethal concentration, 50%
 LD50 = Median lethal dose
 LC0 = lethal concentration, 0%
 LOAEL = lowest-observed-adverse-effect level
 LL50 = Median lethal loading
 LQ = Limited Quantities
 MARPOL = International Convention for the Prevention of Marine Pollution from Ships
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 PBT = Persistent, Bioaccumulative and Toxic substance
 PNEC = Predicted No-Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
 STP = Sewage Treatment Plant
 TLV@TWA = Threshold limit value – time-weighted average
 TLV@STEL = Threshold limit value – short-time exposure limit
 VOC = Volatile Organic Compounds
 vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Modified position

1.2, 1.3, 3.2, 4.3, 5.1, 6.1, 8.1, 8.2, 9.1, 9.2, 11.1, 11.2, 12.6, 12.7, 15.1, 16.2, 16.3