Gear oil 75W - 85 Article number 48785



### Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 10.0. Supersedes version: 8.0

Page 1 / 13

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1 Product identifier

Gear oil 75W - 85 Article number: 48785

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

1 2 1 Relevant uses

Gearbox oil

1.2.2 Uses advised against

None known.

# 1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

**Advisory body** +49 (0)89-19240 (24h) (English)

# **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Eye Irrit. 2: H319 Causes serious eye irritation.

2.2 Label elements

The product is classified as hazardous in accordance to OSHA Standard 29 CFR 1910.1200

(HCS 2012)

Hazard pictograms

<u>(!)</u>

Signal word WARNING

**Hazard statements** H319 Causes serious eye irritation.

**Precautionary statements** P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P280 Wear eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of

disposal.

### 2.3 Other hazards

**Environmental hazards** Does not contain any PBT or vPvB substances.

Contains no ingredients with endocrine-disrupting properties.

Other hazards No particular hazards known.

This product is classified as hazardous in accordance to OSHA Standard 29 CFR 1910.1200.

## Gear oil 75W - 85 Article number 48785



### Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 10.0. Supersedes version: 8.0

Page 2 / 13

# **SECTION 3: Composition / Information on ingredients**

## 3.1 Substances

Not applicable

### 3.2 Mixtures

### The product is a mixture.

Range [%]	Substance
20 - < 25	Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-54-7
1 -< 4,59	Polysulfide, Di-tert-butyl-
	CAS: 68937-96-2
1 - < 3	Aminsalz eines Phosphorsäureesters
0,1 - < 0,25	Imidazoline derivative
	CAS: 95-38-5

**Comment on component parts** For full text of H-statements: see SECTION 16.

Contains less than 3% w/w DMSO-extract (only for mineral oils)

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General information Change soaked clothing.

**Inhalation** Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

**Skin contact** In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

**Eye contact** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

**Ingestion** Do not induce vomiting.

Consult a doctor immediately.

Rinse out mouth and give plenty of water to drink.

# 4.2 Most important symptoms and effects, both acute and delayed

No information available.

# 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to the doctor.

# **SECTION 5: Fire-fighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media Foam, dry powder, water spray jet, carbon dioxide.

Extinguishing media that must not

be used

Full water jet.

# 5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

Nitrogen oxides (NOx).

### Gear oil 75W - 85 Article number 48785



### Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 10.0. Supersedes version: 8.0

Page 3 / 13

## 5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

Cool containers at risk with water spray jet.

### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Some risk of slipping due to spillage of product.

Forms slippery surfaces with water.

## 6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. oil binder).

Dispose of absorbed material in accordance within the regulations.

#### 6.4 Reference to other sections

See SECTION 8+13

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

No special measures necessary if used correctly.

Use only in well-ventilated areas.

Use solvent-resistant equipment.

The product is combustible.

Do not eat, drink or smoke when using this product.

After worktime and before work breaks the affected skin areas must be thoroughly cleaned.

Use barrier skin cream.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

Cloths contaminated with product should not be kept in trouser pockets.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Keep container in a well-ventilated place.

Keep container tightly closed.

# 7.3 Specific end use(s)

See product use, SECTION 1.2

# Gear oil 75W - 85 Article number 48785



# Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 10.0. Supersedes version: 8.0

Page 4 / 13

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (US)

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)

CAS: 64742-54-7

2 mg/kg bw/day

Long-term exposure: 5 mg/m³, OSHA, oil mist

## **DNEL**

Substance		
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7		
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³		
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³		
Industrial, dermal, Long-term - systemic effects, 970 μg/kg bw/day		
general population, inhalative, Long-term - local effects, 1.19 mg/m³		
general population, oral, Long-term - systemic effects, 740 μg/kg bw/day		
Polysulfide, Di-tert-butyl-, CAS: 68937-96-2		
Industrial, inhalative, Long-term - systemic effects, 14.5 mg/m³		
Industrial, dermal, Long-term - systemic effects, 3.33 mg/kg bw/day		
general population, inhalative, Long-term - systemic effects, 2.6 mg/m³		
general population, dermal, Long-term - systemic effects, 1.66 mg/kg bw/day		
Imidazoline derivative, CAS: 95-38-5		
Industrial, inhalative, Long-term - systemic effects, 0.46 mg/m³		
Industrial, inhalative, Acute - systemic effects, 14 mg/m³		
Industrial, dermal, Long-term - systemic effects, 0.06 mg/kg bw/day		
Industrial, dermal, Acute - systemic effects, 2 mg/kg bw/day		

## **PNEC**

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
oral (food), 9,33 mg/kg
Polysulfide, Di-tert-butyl-, CAS: 68937-96-2
freshwater, 0.24 μg/L
seawater, 0.024 µg/L
sewage treatment plants (STP), 4.51 mg/L 4.51 mg/L
sediment (freshwater), 0.94 mg/kg sediment dw 4.51 mg/L
sediment (seawater), 0.094 mg/kg sediment dw 4.51 mg/L
soil, 1513 mg/kg soil dw 4.51 mg/L
Imidazoline derivative, CAS: 95-38-5
freshwater, 30 ng/L
seawater, 3 ng/L
sewage treatment plants (STP), 270 μg/L
sediment (freshwater), 376 µg/kg sediment dw
sediment (seawater), 37.6 μg/kg sediment dw
soil, 75 μg/kg soil dw

### Gear oil 75W - 85 Article number 48785



### Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 10.0. Supersedes version: 8.0

Page 5 / 13

### 8.2 Exposure controls

Additional advice on system design Ensure adequate ventilation on workstation.

General limit for oil mist should be noted.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

Eye protection Safety glasses. (EN 166:2001)

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

> 0,4 mm: Nitrile rubber, >120 min (EN 374-1/-2/-3).

Skin protection Light protective clothing.

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Do not inhale gases/vapors/aerosols. Avoid contact with eyes and skin.

Respiratory protection Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)

Thermal hazards No information available.

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

### **SECTION 9: Physical and chemical properties**

## Information on basic physical and chemical properties

Physical state Liquid **Form** Liquid Color brown Odor characteristic

**Odor threshold** No information available.

pH-value Not applicable Not applicable pH-value [1%] Boiling point or initial boiling point

and boiling range [°C]

Not applicable

Flash point [°C] 215

**Flammability** Not explosive. not self-igniting Lower explosion limit Upper explosion limit Not applicable

**Oxidizing properties** No

Vapor pressure/gas pressure [kPa] No information available.

0,85 (DIN 51757) (15 °C / 59,0 °F) Density [q/cm<sup>3</sup>]

Relative density Not determined Bulk density [kg/m³] Not applicable Solubility in water immiscible

Solubility other solvents No information available. Partition coefficient n-octanol/water

(log value)

No information available.

78 mm<sup>2</sup>/s 40°C (DIN 51562) Kinematic viscosity Relative vapour density No information available. Melting point [°C] No information available.

Auto-ignition temperature [°C] Not applicable

Decomposition temperature [°C] No information available. No information available. Particle characteristics

# Gear oil 75W - 85 Article number 48785



# Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 10.0. Supersedes version: 8.0

Page 6 / 13

## 9.2 Other information

No information available.

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

See SECTION 10.3.

# 10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

# 10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents. Reactions with strong alkalies. Reactions with strong acids.

# 10.4 Conditions to avoid

Strong heating.

# 10.5 Incompatible materials

Strong oxidizing agent. Strong basic compounds strong acids

## 10.6 Hazardous decomposition products

No hazardous decomposition products known.

### Gear oil 75W - 85 Article number 48785



### Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 10.0. Supersedes version: 8.0

Page 7 / 13

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

#### Acute oral toxicity

Product

oral, Based on the information available, the classification criteria have not been fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LD50, oral, Rat, 5000 mg/kg bw

Polysulfide, Di-tert-butyl-, CAS: 68937-96-2

LD0, oral, Rat, 2000 mg/kg bw (OECD 401)

Imidazoline derivative, CAS: 95-38-5

LD50, oral, Rat, 1265 mg/kg

### Acute dermal toxicity

Product

dermal, Based on the information available, the classification criteria have not been fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LD50, dermal, Rabbit, 2000 - 5 00 mg/kg bw

Polysulfide, Di-tert-butyl-, CAS: 68937-96-2

LD0, dermal, Rat, 2000 mg/kg bw (OECD 402)

## Acute inhalational toxicity

inhalative, Based on the information available, the classification criteria have not been fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Serious eye damage/irritation Toxicological data of complete product are not available.

Irritant

Calculation method

Skin corrosion/irritation Based on the information available, the classification criteria have not been fulfilled.

Respiratory or skin sensitisation Based on the information available, the classification criteria have not been fulfilled.

Specific target organ toxicity —

single exposure

Based on the information available, the classification criteria have not been fulfilled.

Specific target organ toxicity —

repeated exposure

Based on the information available, the classification criteria have not been fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day

NOAEL, dermal, Rabbit, 1000 mg/kg bw/day

NOAEC, inhalative, Rat, 980 mg/m3 air

LOAEL, oral, Rat, 125 mg/kg bw/day

Imidazoline derivative, CAS: 95-38-5

### Gear oil 75W - 85 Article number 48785



### Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 10.0. Supersedes version: 8.0

Page 8 / 13

NOAEL, oral, Rat, 20 mg/kg bw/day

Mutagenicity Based on the information available, the classification criteria have not been fulfilled. Reproduction toxicity Based on the information available, the classification criteria have not been fulfilled.

- Fertility

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

- Development

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

Based on the information available, the classification criteria have not been fulfilled. Carcinogenicity **Aspiration hazard** Based on the information available, the classification criteria have not been fulfilled.

**General remarks** 

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

**SECTION 12: Ecological information** 

12.1 Toxicity

Product

Based on the information available, the classification criteria have not been fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

EL50, (48h), Invertebrates, 10 g/L

NOELR, (14d), fish, 1 mg/L

LL50, (96h), Invertebrates, 10 g/L

LL50, (96h), fish, 100 mg/L

Polysulfide, Di-tert-butyl-, CAS: 68937-96-2

LC50, (96h), Danio rerio, >0.088 mg/L (OECD 203)

EC50, (24h), Daphnia magna, >0.27 mg/L (OECD 202)

EC50, (72h), Pseudokirchneriella subcapitata, 2.45 mg/L (OECD 201)

Imidazoline derivative, CAS: 95-38-5

EC50, (48h), Invertebrates, 163 µg/L

EC50, (72h), Algae, 16.9 - 30 µg/L

LC0, (96h), fish, 180 µg/L

12.2 Persistence and degradability

Behaviour in environment

Not determined

compartments

Not determined

Behaviour in sewage plant **Biological degradability** 

Not determined

## Gear oil 75W - 85 Article number 48785



### Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 10.0. Supersedes version: 8.0

Page 9 / 13

### 12.3 Bioaccumulative potential

No information available.

# 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

## 12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

### 12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

## **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

**Product** 

In according to RoHS!

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

RCRA Hazard Class (40CFR 261)

Waste must be disposed of in accordance with federal, state and local environmental control

regulations. Consult your local or regional authorities.

# **SECTION 14: Transport**

## 14.1 UN number

Transport by land according to

ADR/RID

Not applicable

Inland navigation (ADN) Not applicable

Marine transport in accordance with

**IMDG** 

Not applicable

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 Not applicable

CFR)

Gear oil 75W - 85 Article number 48785



### Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 10.0. Supersedes version: 8.0

Page 10 / 13

14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN)

NO DANGEROUS GOODS

**IMDG** 

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

DOT Road Shipment Information (49 Not applicable

CFR)

14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

Not applicable

Inland navigation (ADN)

Not applicable

Marine transport in accordance with Not applicable

**IMDG** 

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 Not applicable

CFR)

14.4 Packing group

Transport by land according to

ADR/RID

Not applicable

Inland navigation (ADN)

Not applicable

Marine transport in accordance with Not applicable

**IMDG** 

Air transport in accordance with IATA Not applicable

DOT Road Shipment Information (49 Not applicable

CFR)

### Gear oil 75W - 85 Article number 48785



### Ferdinand Bilstein GmbH + Co. KG

#### 14.5 Environmental hazards

Transport by land according to

ADR/RID

No

No

Inland navigation (ADN)

Marine transport in accordance with

**IMDG** 

Air transport in accordance with IATA No

DOT Road Shipment Information (49 No

CFR)

### 14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

## 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

### **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### **US Regulations**

National regulations 29 CFR 1910.1200-HCS 2012, OSHA-PEL, ACGIH-TLV, NTP, IARC, SARA Title III, NFPA,

TSCA, California - Prop. 65

SARA, 302 No information available.
 SARA, 311 No information available.
 SARA, 313 No information available.

- TSCA All chemical substances in this material are included on or exempted from listing on the TSCA

Inventory.

- FDA No information available.

American Conference of

Governmental Industrial Hygienists -

ACGIH

Ingredients not listed as carcinogens.

International Agency for Research on No component of this product present at levels greater than or equal to 0.1% is identified as

**Cancer IARC** probable, possible or confirmed human carcinogen by IARC.

National Toxicology Program - NTP No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

**HAP-VOC** No information available.

Transport-regulations DOT-Classification, ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)

# 15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### Gear oil 75W - 85 Article number 48785



### Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 10.0. Supersedes version: 8.0

Page 12 / 13

## **SECTION 16: Other information**

## 16.1 Abbreviations and acronyms:

ACGIH = American Conference of Governmental Industrial Hygienists;

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route;

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses;

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure;

CAS = Chemical Abstracts Service;

CERCLA = Comprehensive Environmental Response, Compensation and Liability Act;

CFR = Code of Federal Regulations;

CPR = Controlled Products Regulations;

DMEL = Derived Minimum Effect Level;

DNEL = Derived No Effect Level;

DOT = Department of Transportation;

EC50 = Median effective concentration;

EPA = Environmental Protection Agency;

GHS = Globally Harmonized System of Classification and Labelling of Chemicals;

IATA = International Air Transport Association;

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk;

IC50 = Inhibition concentration, 50%;

IMDG = International Maritime Code for Dangerous Goods;

IARC = International Agency of Research on Cancer;

IATA = International Air Transport Association;

TSCA = Toxic Substance Control Act;

HMIS = Hazardous Materials Identification System;

NFPA = National Fire Protection Association;

NIOSH = National Institute for Occupational Safety and Health;

OSHA = Occupational Safety and Health Administration;

LC50 = Lethal concentration, 50%;

LD50 = Median lethal dose, 50%;

MARPOL = International Convention for the Prevention of Marine Pollution from Ships;

PBT = Persistent, Bioaccumulative and Toxic substance;

PNEC = Predicted No-Effect Concentration;

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals;

SARA = Superfund Amendments and Reauthorization Act;

TLV®/TWA = Threshold limit value – time-weighted average; TLV®STEL = Threshold limit value – short-time exposure limit;

VOC = Volatile Organic Compounds;

vPvB = very Persistent and very Bioaccumulative;

# 16.2 Ratings

Gear oil 75W - 85 Article number 48785



### Ferdinand Bilstein GmbH + Co. KG

Date printed 21.03.2024, Revision 21.03.2024

Version 10.0. Supersedes version: 8.0

Page 13 / 13

### **NFPA Ratings**



TOP, FLAMMABILITY: 1 - Slight Hazard LEFT, HEALTH: 2 - Moderate Hazard RIGHT, REACTIVITY: 1 - Slight Hazard BOTTOM, SPECIAL NOTICE:

### **HMIS Ratings**



- 2 Moderate Hazard
- 1 Slight Hazard
- 1 Slight Hazard
- X Personal protection rating to be supplied by user depending on use conditions

### PERSONAL PROTECTION:

- A Safety Glasses
- B Safety Glasses and Gloves
- C Safety Glasses, Gloves and Protection Apron
- D Face Shield, Gloves and Protection Apron
- E Safety Glasses, Gloves and Dust Respirator
- F Safety Glasses, Gloves, Protection Apron and Dust Respirator
- G Safety Glasses, Gloves and Vapor Respirator.
- H Splash Goggles, Gloves, Protection Apron and Vapor Respirator.
- I Safety Glasses, Gloves, Dust Respirator and Vapor Respirator.
- J Splash Goggles, Gloves, Protection Apron, Dust Respirator and Vapor Respirator.
- K Airline Mask or Hood, Gloves, Full Suit and Boots.
- X Personal protection rating to be supplied by user depending on use conditions

## **Modified position**

None